
TRACTION BATTERY 3PzS450 (2V450Ah)







CHARACTERISTICS

Item		Specifications
Rated Voltage		2\
Capacity@25°C (86°F)	C₅,1.70V/cell	450Ał
Dimension	Length	65mm (2.56inches)
	Width	198mm (7.80inches)
	Container Height	720mm (28.3inches)
	Total Height	752mm (29.6inches)
Approx Weight	Without Electrolyte	18.8kg (41.4lbs)
	With Electrolyte	25.3kg (55.8lbs)
Terminal		M10
Container Material		PP
Max. Discharge Current (5	s)	8C
Operating Temp. Range	Discharge	-15~55°C(5~131°F
	Charge	0~50°C(32~122°F
	Storage	5~40°C(41~104°F
Cycle life		≥1200 cycles
Cycle Use	Initial Charging Current	less than 0.14C
	Voltage 2.	60V-2.65V at 25°C(77°F
	Temp. Coeffcient	-5mV/°C
Capacity affected by Temperature	40°C(104°F)	103%
	30°C(86°F)	100%
	0°C(32°F)	86%
Self Discharge	Less than 8% C ₅ after storing 28 days at 20°C, and then a freshening charge is required.	
	For higher temperature, the time interval will be shorter.	

APPLICATIONS


- Forklift
- Traction vehicle
- Transportation vehicle
- Tram
- Bus
- Gymnastic and recreation location


GENERAL FEATURES


- Nonwoven protective gauntlet, better elastic property, less pore size, less electrical resistance and higher air permeability
- Flexible, fully isolated connector prevents any creeping current
- Flip top plugs with special electrolyte level indication
- Automatic refilling plugs are also available (according request)
- Imported microporous catercorne rseparator with advanced quality provides higher porosity and lower electrical resistance
- · Containers and lids are made of polypropylene (PP)The impact resistance is very good
- · Patented terminal sealing construction fully prevents plate growth and electrolyte leakage

TRACTION BATTERY 3PzS450 (2V450Ah)













Leoch International Technology Ltd.

Leoch Batteries Pte Ltd









Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.