FLOODED BATTERY

56825 (12V68Ah)





CHARACTERISTICS


| Item | | Specifications |
|--------------------------------|--------|-------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity (20HR) | | 68Ah |
| Reserve Capacity | | 114min |
| Cold Cranking Amps@0°F (-18°C) | | 550A |
| | Length | 314mm(12.4inches) |
| Dimension | Width | 174mm(6.85inches) |
| | Height | 174mm(6.85inches) |
| Approx Weight | | 17.7kg(39.0lbs) |
| Terminal | | 1 |
| Cell layout | | 0 |
| Hold-Down | | B13 |
| Case | | Black-PP Material |
| Cover | | Black-PP Material |
| Handle | | TS6 |


APPLICATIONS

- Car start
- •EV/HEV
- •Engine start

GENERAL FEATURES

- ·High capacity and high CCA
- ·Long life
- •Advanced lead-calcium alloy technology, maintenance-free design
- •Patented venting system bring less water loss and prevent acid leakage
- •OE quality certification





Leoch International Technology Ltd.

@ www.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.



^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.