

MAINTENANCE-FREE MOTORCYCLE BATTERY

EB9-4-I (12V8Ah)










CHARACTERISTICS

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		8Ah
Cold Cranking Perfo	rmance Amps@0°F (-18°	°C) 110A
Dimension (±2mm)	Length	150mm (5.91inches)
	Width	87mm (3.43inches)
	Container Height	105mm (4.13inches)
	Total Height	105mm (4.13inches)
Battery (with acid)	Approx Weight	2.85kg (6.28lbs)
Terminal type		A
Battery type	Factory Activated Serie	es
Full Charge	Constant-Voltage Charge:	
	Initial charging current	Less than 0.3C10
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	15~18h
	Constant-Current Cha	rge:
	Charging current 0.1C ₁₀ , when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	Initial charging current	Unlimited
	Voltage 13.50V~13.80V at 25°C (77°F)	
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

Discharge Characteristics (25°C, 77°F)



*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.

GENERAL FEATURES

· Sealed and non-spillable AGM battery

· Shipped pre-charged and ready to install

• Maintenance-free

Leoch Batteries Pte Ltd

Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved.Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.