

# DT SERIES FLOODED BATTERY


# DT136 (6V245Ah)
















Designed in compliance with applicable BCI standard. Tested in compliance to BCI standard.

Leoch International Technology Ltd. @ www.leoch.com

Leoch Batteries Pte Ltd m www.leoch.sg

#### **CHARACTERISTICS**


Item		Specifications
Voltage		6V
Dimension	Length	244mm (9.61inches)
	Width	191mm (7.52inches)
	Container Height	246.5mm (9.70inches)
	Total Height	268mm (10.6inches)
Approx Weight		31kg (68.3lbs)
Terminal		1 (AP)
Container Material		PP
Rated Capacity	20HR	245Ah
	5HR	201Ah
Reserve Capacity	25A	500min
	75A	135min

## **GENERAL FEATURES**

- · Long cycle service life, strong recovery ability of deep discharge
- · Low risk of thermal runaway, easy maintenance
- High energy, low internal resistance, low self-discharge
- · Reliable sealing structure ensures no leakage during use
- · Special design and structure increase battery performance
- · The special alloy improves the corrosion resistance of the plate increases the service life and good deep discharge performance

## **APPLICATIONS**

- · Electric vehicle
- Golf cart
- · Sightseeing bus
- · Cleaning equipment
- AWP Marine&RV



Leoch Battery Corporation @ www.leoch.us

Leoch Europe S.A. www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-DT136-PD-EN-V1.0-20230719