MARINE AGM DUAL PURPOSE BATTERY LPM12-170M (12V170Ah)





CHARACTERISTICS

| Item | | Specifications |
|--------------------------------|--------|--------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity (20HR) | | 170Ah |
| Reserve Capacity | | 380min |
| Cold Cranking Amps@0°F (-18°C) | | 900A |
| Dimension | Length | 512mm (20.2inches) |
| | Width | 222mm (8.74inches) |
| | Height | 216mm (8.50inches) |
| Approx Weight | | 50.5kg (111.3lbs) |
| Terminal | | 5 |
| Cell layout | | 3 |
| Hold-Down | | B0 |
| Case | | Black-PP Material |
| Cover | | Black-PP Material |
| Handle | | TS8 |


APPLICATIONS

•MARINE and RV


•Start and deep cycle


GENERAL FEATURES

- •Superior starting and cycling performance
- High capacity and high CCA
- •2x faster charge acceptance than conventional starter batteries
- •3x higher cycle life than conventional starter batteries
- ·Advanced Absorbed Glass Mat (AGM) technology











*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.

Leoch Batteries Pte Ltd

Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-LPM12-170M-PD-EN-V1.2-20241219