
## **MAINTENANCE-FREE MOTORCYCLE BATTERY**

EB14A-4(J) (12V12Ah)







## **CHARACTERISTICS**

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		12Ah
Cold Cranking Perfo	rmance Amps@0°F (-18	°C) 170A
Dimension (±2mm)	Length	133mm (5.24inches)
	Width	90mm (3.54inches)
	Container Height	164mm (6.46inches)
	Total Height	164mm (6.46inches)
Battery (with acid)	Approx Weight	4.2kg (9.26lbs)
Terminal type		A
Battery type	Factory Activated Ser	ies
Full Charge	Constant-Voltage Charge:	
	Initial charging curren	t Less than 0.3C <sub>10</sub>
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	15~18h
	Constant-Current Cha	arge:
	Charging current $0.1C_{10}$ , when charging voltage up to $14.40V$ , continue to charge $4h$	
Floating Charge	Initial charging curren	t Unlimited
	Voltage	13.50V~13.80V at 25°C (77°F)
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

## **GENERAL FEATURES**

- Maintenance-free
- · Sealed and non-spillable AGM battery
- · Shipped pre-charged and ready to install

## Discharge Characteristics (25°C, 77°F) 12.0 10.5 Loading Voltage (V) 7.0 5 10 15 30 60 2 3 10 20 min Discharge Time

Leoch International Technology Ltd.

m www.leoch.com

**Leoch Batteries Pte Ltd** www.leoch.sg

**Leoch Battery Corporation** mww.leochamericas.com

Leoch Europe S.A.



<sup>\*</sup>Values are subject to variation of +/- 5% in normal manufacturing processes.