
MAINTENANCE-FREE MOTORCYCLE BATTERY

EB30-3-1(J) (12V30Ah)







Top View

⊕

GENERAL FEATURES

· Sealed and non-spillable AGM battery


· Shipped pre-charged and ready to install

• Maintenance-free

CHARACTERISTICS

ltem		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		30Ab
Cold Cranking Perfo	rmance Amps@0°F (-18°	°C) 330A
Dimension (±2mm)	Length	166mm (6.54inches)
	Width	126mm (4.96inches)
	Container Height	173mm (6.81inches)
	Total Height	173mm (6.81inches)
Battery (with acid)	Approx Weight	8.88kg (19.6lbs)
Terminal type		А
Battery type	Factory Activated Seri	es
Full Charge	Constant-Voltage Charge:	
	Initial charging current	Less than 0.3C10
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	15~18h
	Constant-Current Cha	irge:
	Charging current $0.1C_{10}$, when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	Initial charging current	Unlimited
	Voltage 13.50V~13.80V at 25°C (77°F)	
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

Discharge Characteristics (25°C, 77°F)



*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd. @ www.leoch.com

Leoch Batteries Pte Ltd @ www.leoch.sg

Leoch Battery Corporation www.leochamericas.com

Leoch Europe S.A. www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-EB30-3-1(J)-PD-EN-V1.0-20240507