


Starter batteries for motorcycles

LFPS-X14 [12.8V4Ah]

Physical Specification

Nominal Voltage	12.8V	
Nominal Capacity (10Hr)	4.0 Ah	
Dimension	Length	150±2mm (5.91 inches)
	Width	87±2mm (3.43 inches)
	Container Height	93±2mm (3.66 inches) Total
	Height (with Terminal)	93±2mm (3.66 inches)
Weight	Approx 0.70kg (1.54lbs)	

- * Motorcycle Li-ion battery
- * Maintenance-free
- * Real-time protection (overcharge, over-discharge, over-temperature) and energy balance of battery system through BMS
- * Powerful 120 cold cranking amps
- * Shipped pre-charged and ready to install
- * Replaces YTX14H-BS/KMX14-BS/YTX14-BS/HVT-8 battery



Dimensions (mm)

Electrical Specification

Rated Capacity	0.1C rate (0.4A)	4.0Ah
	0.5C rate (2.0A)	4.0Ah
	10C rate (40.0A)	3.6Ah
	30C rate (120.0A)	5S
Capacity affected by Temperature	40 °C (104 °F)	98%
	25 °C (77 °F)	100%
	0 °C (32 °F)	85%
	-20 °C (-4 °F)	60%
Self Discharge	Approximately 1.5% per month (25°C (77°F))	
Charging Methods	Constant-Voltage Charge:	
	Full Charge Initial charging current: less than 2.0A Voltage: 14.40 V ~ 14.60 V at 25 °C (77 °F)	



Curve Specification

