

Lithium Iron Phosphate (LiFePO4) Battery

Features Of LiFePO4 Battery


Longer Cycle Life: Offers up to 20 times longer cycle life and five times longer float/calendar life than lead acid battery, helping to minimize replacement cost and reduce total cost of ownership.

Lighter Weight: About 40% of the weight of a comparable lead acid battery. A 'drop in' replacement for lead acid batteries.

Higher Power: Delivers twice power of lead acid battery, even high discharge rate, while maintaining high energy capacity.

Wider Temperature Range: -20°C~60°C.

Superior Safety: Lithium Iron Phosphate chemistry eliminates the risk of explosion or combustion due to high impact, overcharging or short circuit situation.



Specification



LFeLi-2433M (25.6V33Ah)

Application


- Electric vehicles, electric mobility
- Solar/wind energy storage system
- Telecommunication
- Medical equipment
- Lighting

Electrical Characteristics	Nominal Voltage	25.6V
	Nominal Capacity	33Ah
	Energy	844Wh
	Internal Resistance(AC)	≤ 20m Ω
	Cycle Life	>3000 cycles @0.5C 80%DOD
	Months Self Discharge	<3%
	Efficiency of Charge	100% @0.5C
	Efficiency of Discharge	96~99% @1C
Standard Charge	Charge Voltage	29.2±0.2V
	Charge Mode	0.2C to 29.2V, then 29.2V, charge current to 0.02C (CC/CV)
	Charge Current	18A
	Max. Charge Current	33A
	Charge Cut-off Voltage	29.2V±0.2V
Standard Discharge	Rated Discharge Current	18A
	Max.Discharge Current	33A
	Discharge Cut-off Voltage	20V ·
Environmental	Charge Temperature	0 °C to 55 °C (32F to 131F) @60 \pm 25% Relative Humidity
	Discharge Temperature	–20 $^\circ$ C to 60 $^\circ$ C (–4F to 140F) $@60\pm25\%$ Relative Humidity
	Storage Temperature	0 $^\circ C$ to 45 $^\circ C$ (32F to 113F) $@60 \pm 25\%$ Relative Humidity
	IP Class	IP65
Mechanical	Plastic Case	ABS
	Dimensions (in./mm.)	260*168*214mm (10.24"*6.61"*8.43")
	Weight (lbs./kg.)	6.2kg (13.64lbs)
	Terminal	M6







Different Rate Discharge Curve(25℃)




State of Charge Curve(0.5C, 25°C




Different DOD Discharge Cycle Life Curve(0.5C)




Different Temperature Discharge Curve(0.5C)



Charging Characteristics(0.5C, 25℃)



Different Temperature Self Discharge Curve



Publication No :LB-LFeLi-2433M-PD-EN-V2.0-202208

© 2022 LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted. Subject to revisions without prior notice.



Http//:www.leoch.com

Libattery@leoch.com

Leoch International Technology Limited

Add:5th Floor, Xinbaohui Bldg., Nanhai Blvd, Nanshan, Shenzhen, China. 518054

