Lithium Battery -Forklift Series

FP24-200



Features Of LiFePO4 Battery

- Long cycle life;
- High integration, small size, high energy density;
- Intelligent management of product usage status with high security;
- Environmental protection;
- Capable of 1C fast charging;

Application scenarios

- Forklift;
- Lead-acid battery to lithium battery vehicles;
- Industrial control products;
- Rescue vehicles such as scissor forklifts;



| Specification | |
|--------------------------|--------------------------------|
| Nominal Voltage | 25.6V |
| Working Voltage | 20-29.2V |
| Nominal Capacity | 206Ah |
| Energy | 5273Wh |
| Self Discharge | ≤3% Per Month |
| IP Grade | IP65 |
| Positive material | Lithium ironphosphate |
| Cell type | Prismatic |
| Combination method | 106Ah,1P8S |
| Weight | ABOUT 45.0KG |
| Dimension LxWxH | L495*W290*H268mm |
| Fixed size | NO |
| Terminal Type | anderson connector,120A |
| Shell type | Powder Coated Steel |
| Handle | YES |
| Storage Temp. short term | -20-50 ℃ |
| Storage Temp. long term | 5~35 ℃ |
| Cycle Life | 5000 cycles |
| Heating function | No |
| Cooling type | No |
| Insulation | 20MΩ/1000VDC, @25±5℃, RH50% |
| Certification(Program) | UN38.3 |

| Charging | |
|----------------------------|---------------|
| Charging Freeze Protection | <0°C |
| Recom. Charging Current | 100A |
| Upper limit voltage | 29.2V |
| Charging Temp. Range | 0~55 ℃ |

| DisCharging | |
|--------------------------|-----------|
| Max Continuous Discharge | 200A |
| Max Discharge current | 412A@30S |
| Lower limit voltage | 20.0V |
| BMS Voltage Recovery | 44.8V |
| Discharge Temp. Range | -20-60 °C |

Function (optional)

(CAN/RS485), Bluetooth, 4G, Screen, Charger

Physical Dimension-mm

