

# Residential Energy Storage Battery (Wall-mounted)



LW51.2-200



**High Efficiency**

Max. efficiency 95%



**Eco-Friendly**

Clean energy



**Long Lifespan**

Sustainable long cycles



**Built-in BMS**

Charge & discharge protection

## Product Introduction



Up to 16 groups of parallel connections, flexible capacity expansion



LED display for voltage, current, temperature, convenient for users to query



Compatible with mainstream inverters in the market, providing more options



Built-in BMS provides multiple protection functions

Item	Parameters
Specifications and models	LW-51.2-200
Nominal voltage	51.2v
Nominal capacity	200Ah
Maximum continuous charge/ discharge current"	100A/100A
Discharge voltage/Maximum charge	43.2 V/58.4 V
Weight	94kg
Dimensions(W×D×H) (mm)	500x620x245
Cycle life	5000 cycles at 80% DOD
Number of parallel connections supported"	16
Self-discharge (month)@25°C	≤3%
BMS communication types	RS485/RS232/CAN
Cooling Mode	Free Cooling
IP Class	IP54
Display Fuction	LCD Display
Design Life	15 Years
Testing and Certification	CE UN38.3 UL IEC
Storage Temperature	0°C to 40°C
Operate Temperature	charge: 0°C to 45°C; discharge: -10°C to 55°C
Relative Humidity	5% to 95%
Working Pressure	61kPa~113kPa